


# Taking reversed phase chiral separations to a new level – Kromasil® CelluCoat™ RP

Designed to give you a highly efficient chiral stationary phase for reversed phase chiral chromatography. No pressure limits\* and the unique 3 µm particles enable fast, efficient and high resolution analyses. Kromasil CelluCoat RP is based on the same in-house developed silica matrix and the same selector, tris-[3,5-dimethylphenyl] carbamoyl cellulose as Kromasil CelluCoat.

## Faster baseline separations




## Recommended mobile phases for Kromasil CelluCoat RP

Type of compound	Aqueous solution	Organic modifier	Org. modifier part range	Temperature range
Acidic	<ul style="list-style-type: none"> <li>– 50 mM Phosphate buffer, pH 2.0</li> <li>– Phosphoric acid, aqueous solution, pH 2.0</li> <li>– 100 mM Aqueous hexafluorophosphate solution, pH 2.0</li> <li>– 0.1% Acetic acid</li> </ul>	Acetonitrile, methanol, ethanol, 2-propanol	10 – 85%	5 – 40°C
Neutral	<ul style="list-style-type: none"> <li>– Water</li> <li>– 100 mM Aqueous hexafluorophosphate solution</li> </ul>	Acetonitrile, methanol, ethanol, 2-propanol	10 – 100%	5 – 40°C
Basic	<ul style="list-style-type: none"> <li>– 20 mM Borate buffer, pH 9.0</li> <li>– 20 mM Phosphate buffer, pH 8.0</li> <li>– 100 mM Aqueous hexafluorophosphate solution</li> </ul>	Acetonitrile, methanol, ethanol, 2-propanol	10 – 85%	5 – 25°C

\*Kromasil CelluCoat RP can withstand flow rates equivalent to pressures of up to 400 bar – i.e. the approximate limit for most HPLC systems.


# Kromasil CelluCoat RP Applications

## Indapamide




### Conditions:

Stationary phase: Kromasil CelluCoat RP, 3  $\mu$ m  
Column: 4.6  $\times$  150 mm  
Mobile phase: Acetonitrile/Water (40/60)  
Flow rate: 0.5 ml/min  
Temperature: 22°C  
Detection: UV 254 nm




$k'_1$  3.02  
 $k'_2$  4.69  
 $N_1$  58900  
 $N_2$  30900  
 $\alpha$  1.6  
 $R_s$  6.6

## 4-Phenyl-2-butanol




### Conditions:

Stationary phase: Kromasil CelluCoat RP, 3  $\mu$ m  
Column: 4.6  $\times$  150 mm  
Mobile phase: Acetonitrile/Water (40/60)  
Flow rate: 0.5 ml/min  
Temperature: 22°C  
Detection: UV 220 nm




$k'_1$  1.48  
 $k'_2$  1.71  
 $N_1$  105900  
 $N_2$  104400  
 $\alpha$  1.2  
 $R_s$  2.8

## Pindolol




### Conditions:

Stationary phase: Kromasil CelluCoat RP, 3  $\mu$ m  
Column: 4.6  $\times$  150 mm  
Mobile phase: Acetonitrile/Water, 50 mM sodium borate (40/60)  
Flow rate: 0.5 ml/min  
Temperature: 22°C  
Detection: UV 254 nm




$k'_1$  1.09  
 $k'_2$  3.04  
 $N_1$  88800  
 $N_2$  42200  
 $\alpha$  2.8  
 $R_s$  14.2

## Warfarin



### Conditions:

Stationary phase: Kromasil CelluCoat RP, 3  $\mu$ m  
Column: 4.6  $\times$  150 mm  
Mobile phase: Acetonitrile/Water, 100 mM phosphoric acid (40/60)  
Flow rate: 0.5 ml/min  
Temperature: 22°C  
Detection: UV 254 nm



$k'_1$  4.15  
 $k'_2$  6.72  
 $N_1$  92700  
 $N_2$  77400  
 $\alpha$  1.6  
 $R_s$  11.2

## Availability

Kromasil CelluCoat RP is available in 3  $\mu$ m as pre-packed columns. The standard dimensions are 4.6  $\times$  50 mm and 4.6  $\times$  150 mm. Other column dimensions are available upon request.

## Product codes

Kromasil 3-CelluCoat RP 4.6  $\times$  50 mm

Kromasil 3-CelluCoat RP 4.6  $\times$  150 mm

Eka Chemicals AB, Separation Products, SE-445 80 Bohus, Sweden.  
Tel. +46 31 58 70 00 Fax +46 31 58 77 27

NAFTA countries: Akzo Nobel / Eka Chemicals Inc.  
281 Fields Lane, Brewster, NY 10509, U S A.  
Tel. +1 845 276 8223 Fax +1 845 277 1406

China: Akzo Nobel / Eka Chemicals  
No. 12 Yumin Rd., Chaoyang District, Beijing 100029, China.  
Tel. +86 10 82251233 Fax +86 10 82251911  
Cell +86 133 8116 7168

kromasil@eka.com

www.kromasil.com

